



型号	蓄能器	泵	电机工作电压	电气设备	D	F	H	重量	过滤器附件
	L	型号	V	型号					型号
DO 20V VTL 5	20	VTL 5	3 ~ 230/400-50Hz	DO 06 97V	320	345	360	38.5	FB 20 / FC 20
DO 20V VTL 5 M	20	VTL 5 M	1 ~ 230/50Hz	DO 06 98V	320	345	360	39.0	FB 20 / FC 20
DO 20V VTL 10	20	VTL 10	3 ~ 230/400-50Hz	DO 06 97V	352	345	360	44.5	FB 20 / FC 20
DO 20V VTL 10 M	20	VTL 10 M	1 ~ 230-50Hz	DO 06 98V	352	345	360	45.0	FB 20 / FC 20
DO 20V VTL 10/FG	20	VTL 10/FG	3 ~ 230/400-50Hz	DO 06 97V	390	360	360	49.0	FB 20 / FC 20
DO 20V VTL 10/FG M	20	VTL 10/FG M	1 ~ 230-50Hz	DO 06 98V	390	360	360	49.5	FB 20 / FC 20
DO 20V VTL 15/FG	20	VTL 15/FG	3 ~ 230/400-50Hz	DO 06 97V	410	360	360	51.0	FB 20 / FC 20
DO 20V VTL 15/FG M	20	VTL 15/FG M	1 ~ 230-50Hz	DO 06 98V	410	360	360	51.5	FB 20 / FC 20
DO 20V RVP 15	20	RVP 15	3 ~ 230/400-50Hz	DO 06 97V	350	335	360	39.0	FB 20 / FC 20
DO 20V RVP 15 M	20	RVP 15 M	1 ~ 230-50Hz	DO 06 98V	335	335	360	39.5	FB 20 / FC 20
DO 20V VTL 20/FG	20	VTL 20/FG	3 ~ 230/400-50Hz	DO 06 97V	430	360	360	54.0	FB 20 / FC 20
DO 20V VTL 20/FG M	20	VTL 20/FG M	1 ~ 230-50Hz	DO 06 98V	430	360	360	54.5	FB 20 / FC 20
DO 20V RVP 21	20	RVP 21	3 ~ 230/400-50Hz	DO 06 97V	430	315	360	42.5	FB 20 / FC 20
DO 20V RVP 21 M	20	RVP 21 M	1 ~ 230-50Hz	DO 06 98V	430	315	360	43.0	FB 20 / FC 20

注意：所有型号为RVP...的泵，其标配都包含一个FC...过滤器，适合真空线路的大小。