

MAXIGRIP “抓取王” 真空吸盘的变径接头

这些标准配件为用户提供了MAXIGRIP抓取王真空吸盘的不同装配选择。这种镀锌钢材质的变径接头可将内螺纹标准接头与外螺纹相连接，管螺纹与公制螺纹相连接。六角形内壁结构方便接头的拧紧。



用于VRP吸盘的MF变径接头

型号	D Ø	d Ø	F	H	承插焊	重量 g
00 08 215	G3/8"	G1/4"	8	14	6	11.5

用于VRS - VEP - VES吸盘的MF变径接头

型号	D Ø	d Ø	F	H	承插焊	重量 g
00 08 216	G3/8"	G1/4"	8	11.5	6	6.0

用于VRP吸盘的MM变径接头

型号	D Ø	d Ø	E	F	承插焊	重量 g
00 08 217	G1/4"	G1/4"	15	10	6	16.7
00 08 218	G1/4"	M10 x 1.5	15	12	6	10.2
00 08 219	G1/4"	M14 x 1.5	15	12	6	16.0
00 08 220	G3/8"	G1/4"	14	10	6	18.4
00 08 221	G3/8"	M10 x 1.5	14	12	6	16.3
00 08 222	G3/8"	M14 x 1.5	14	12	6	22.5

用于VRS - VEP - VES吸盘的MM变径接头

型号	D Ø	d Ø	E	F	承插焊	重量 g
00 08 223	G1/4"	G1/4"	11.5	10	6	13.9
00 08 224	G1/4"	M10 x 1.5	13.0	12	6	10.1
00 08 225	G1/4"	M14 x 1.5	13.0	12	6	15.8
00 08 226	G3/8"	G1/4"	10.5	11	6	16.6
00 08 227	G3/8"	M10 x 1.5	10.5	13	6	14.2
00 08 228	G3/8"	M14 x 1.5	10.5	13	6	20.2

