




## GAS - NPT适配接头


这些适配接头可将NPT螺纹管接头连接到GAS螺纹真空组件，如：吸盘支撑块、阀门及电磁阀、过滤器等。



GAS内螺纹-NPT外螺纹适配接头

型号	A Ø	D Ø	E	F	H	T	适配接头 材质	重量 g
00 08 259	1/8" NPT	G1/8"	10	12	22	14	黄铜	14
00 08 260	1/4" NPT	G1/4"	12	17	29	19	黄铜	34
00 08 261	3/8" NPT	G3/8"	16	18	34	22	黄铜	48
00 08 262	1/2" NPT	G1/2"	17	19	36	27	黄铜	72
00 08 263	3/4" NPT	G3/4"	19	20	39	32	黄铜	100
00 08 264	1" NPT	G1"	22	20	42	41	黄铜	176
00 08 265	1" 1/4 NPT	G1" 1/4	23	23	46	50	黄铜	274
00 08 266	1" 1/2 NPT	G1" 1/2	23	23	46	60	黄铜	470
00 08 267	2" NPT	G2"	25	24	49	70	黄铜	506

注意：所有适配器均按最小供应批次制造，并进行定期结算。



GAS外螺纹-NPT内螺纹适配接头

型号	A Ø	D Ø	E	F	H	T	适配接头 材质	重量 g
00 08 268	G1/8"	1/8" NPT	10	15	25	14	黄铜	16
00 08 269	G1/4"	1/4" NPT	11	17	28	19	黄铜	34
00 08 270	G3/8"	3/8" NPT	12	22	34	22	黄铜	52
00 08 271	G1/2"	1/2" NPT	14	23	37	27	黄铜	78
00 08 272	G3/4"	3/4" NPT	14	24	38	32	黄铜	110
00 08 273	G1"	1" NPT	17	28	45	41	黄铜	224
00 08 274	G1" 1/4	1" 1/4 NPT	18	28	46	50	黄铜	290
00 08 275	G1" 1/2	1" 1/2 NPT	19	29	48	60	黄铜	476
00 08 276	G2"	2" NPT	20	31	51	70	黄铜	550

注意：所有适配器均按最小供应批次制造，并进行定期结算。

换算：N (牛顿) = Kg x 9.81 (重力)； 1英寸 = 25.4mm； 1磅= 453.6克 = 0.4536千克